





ULTRA MINIATURE SMD HCMOS OSCILLATOR (1.6 x 1.2 x 0.7mm)
FEATURES:

- WIDE FREQUENCY RANGE
- LOW VOLTAGE / LOW CURRENT
- THE WORLD'S SMALLEST QUARTZ CRYSTAL OSCILLATOR


■ SPECIFICATION

FREQUENCY RANGE		1.000MHz ~ 80.000MHz
FREQUENCY STABILITY		±15ppm ~ ±100ppm
OPERATING TEMPERATURE RANGE		STD: 0°C ~ 70°C, Option: -40°C ~ 85°C (See P/N guide for other options)
STORAGE TEMPERATURE RANGE		-55°C ~ 125°C
SUPPLY VOLTAGE ±10%		1.8V _{DC} ~ 3.3V _{DC}
SUPPLY CURRENT		2.0mA max.
OUTPUT	LOGIC FAMILY	HCMOS
	LOAD	15pF
	LEVEL LOGIC '1' (V_{OH})	V _{DD} - 0.4V min.
	LEVEL LOGIC '0' (V_{OL})	0.4 V max.
	SYMMETRY(DUTY CYCLE)	STD: 40% / 60% @ 1/2V _{DD} level, Option: 45% / 55%
	RISE AND FALL TIME (Tr/Tf)	5nS max.
	START-UP TIME	5mS max.
STAND-BY VOLTAGE	ENABLE (V_{IH})	0.7 x V _{DD} ≤ V _{IH} ≤ V _{DD} or N/C
	DISABLE (V_{IL})	V _{IL} ≤ 0.3 x V _{DD}
ENABLE DELAY TIME		10mS max.
DISABLE DELAY TIME		10mS max.
AGING @ 25°C ± 3°C		±3.0ppm / 1 st year max.
PHASE JITTER RMS (12kHz ~ 5MHz)		1.0pS max.

■ PACKAGE DIMENSIONS

■ SOLDER PATTERN

■ REFLOW PROFILE

■ PART NUMBERING GUIDE


Transko Electronics, Inc reserves the right to make changes to the product (s), service (s), and specification (s) described herein without notice. See "Terms of Sale" for details on our website.